

Transient Earth Fault Relay SIPROTEC 7SN600

Product description	Variants	Order No.
Transient earth-fault relay	Rated frequency 50 Hz	1 2 3 4 5 6 7 8 9 10 11 12 7 S N 6 0 0 0 - □ □ A 0 0
	<u>Rated auxiliary voltage</u> DC 60 V to 250 V, AC 100 V to 220 V without switchover DC 24 V to 48 V	↑ 0 1 B D E
	<u>In 7XP20 housing</u> for panel Surface-mounting with terminals on the side for panel Surface-mounting with terminals at top/bottom part for panel Flush-mounting or cubicle mounting	

Breaker Failure Protection SIPROTEC 7SV600

Product description	Variants	Order No.
Numerical breaker failure protection relay		1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 7 S V 6 0 0 □ - □ □ A 0 0 - □ D A 0
3-pole, 2 stages		↑ 1 5 2 4 5 6 B D E 0 1
	<u>Current transformer</u> 1 A ¹⁾ , 50/60 Hz 5 A ¹⁾ , 50/60 Hz	
	<u>Auxiliary voltage</u> DC 24 V, DC 48 V DC 60 V, DC 110 V, DC 125 V ²⁾ DC 220 V, DC 250 V ²⁾ , AC 115 V, 50 / 60 Hz AC 230 V, 50/60 Hz	
	<u>In 7XP20 housing</u> for surface mounting, terminals located at the side terminals located top and bottom for flush mounting/cubicle mounting	
	3-pole trip 1-/ 3-pole trip	

1) Rated current 1/5A can be selected by means of jumpers.

2) Transition between the two auxiliary voltage ranges can be selected by means of jumpers.